

A—OVERALL LENGTH		B IMMERSION LENGTH	KILO- WATTS	VOLTS	PHASE	FIG. 1 CATALOG NUMBER	FIG. 2 CATALOG NUMBER
STANDARD FIG. 1	IN-LINE FIG. 2						
13 ¹ / ₁₆	16 ¹ / ₁₆	9 ¹ / ₁₆	3	208	1	DWK-S-0001	DWK-I-0001
				208	3	DWK-S-0002	DWK-I-0002
				240	1	DWK-S-0003	DWK-I-0003
				240	3	DWK-S-0004	DWK-I-0004
18 ¹ / ₁₆	21 ¹ / ₁₆	13 ¹ / ₁₆	5	480	3	DWK-S-0005	DWK-I-0005*
				208	1	DWK-S-0006	DWK-I-0006
				208	3	DWK-S-0007	DWK-I-0007
				240	1	DWK-S-0008	DWK-I-0008
20 ¹ / ₁₆	23 ¹ / ₁₆	15 ¹ / ₁₆	6	240	3	DWK-S-0009	DWK-I-0009
				240	3	DWK-S-0010	DWK-I-0010*
				208	1	DWK-S-0011	DWK-I-0011
				208	3	DWK-S-0012	DWK-I-0012
23 ¹ / ₁₆	26 ¹ / ₁₆	19	7.5	240	1	DWK-S-0013	DWK-I-0013
				240	3	DWK-S-0014	DWK-I-0014
				480	3	DWK-S-0015	DWK-I-0015*
				208	1	DWK-S-0016	DWK-I-0016
27 ¹ / ₁₆	30 ¹ / ₁₆	22 ¹ / ₁₆	9	208	3	DWK-S-0017	DWK-I-0017
				240	1	DWK-S-0018	DWK-I-0018
				240	3	DWK-S-0019	DWK-I-0019
				480	3	DWK-S-0020	DWK-I-0020*
30 ¹ / ₁₆	33 ¹ / ₁₆	25 ¹ / ₁₆	10	208	1	DWK-S-0021	DWK-I-0021
				208	3	DWK-S-0022	DWK-I-0022
				240	1	DWK-S-0023	DWK-I-0023
				240	3	DWK-S-0024	DWK-I-0024
30 ¹ / ₁₆	33 ¹ / ₁₆	25 ¹ / ₁₆	10	480	3	DWK-S-0025	DWK-I-0025*
				208	3	DWK-S-0026	DWK-I-0026*
				240	3	DWK-S-0027	DWK-I-0027*
				480	3	DWK-S-0028	DWK-I-0028*

*Requires use of external contactor