

CORROSIVE SOLUTIONS, HEAT TRANSFER LIQUIDS, DEGREASING SOLUTION HEATING – 23 watts/sq. in.

4" 150 LB ASA STAINLESS STEEL FLANGE				CATALOG NUMBERS	
KILOWATTS	VOLTS 3 PHASE	NUMBER OF CIRCUITS	B IMMERSION LENGTH	FIG. 22	FIG. 23
7.5	240	1	16½	H4A-6-0221-M1	H4A-6-0221-M7
10	240	1	19½	H4A-6-0222-M1	H4A-6-0222-M7
12.8	240	1	24½	H4A-6-0223-M1	H4A-6-0223-M7
	480			H4A-6-0224-M1	H4A-6-0224-M7
15.8	240	1	30	H4A-6-0225-M1	H4A-6-0225-M7
	480			H4A-6-0226-M1	H4A-6-0226-M7
19	240	1	35	H4A-6-0228-M1	H4A-6-0228-M7
	480			H4A-6-0229-M1	H4A-6-0229-M7
25	240	2	45½	H4A-6-0230-M1	H4A-6-0230-M7
	480	1		H4A-6-0231-M1	H4A-6-0231-M7
32.3	240	2	56	H4A-6-0232-M1	H4A-6-0232-M7
	480	1		H4A-6-0233-M1	H4A-6-0233-M7

6" 150 LB ASA STAINLESS STEEL FLANGE				CATALOG NUMBERS		
KILOWATTS	VOLTS 3 PHASE	NUMBER OF CIRCUITS	B IMMERSION LENGTH	FIG. 24	FIG. 25	FIG. 26
19	240	5	16½	H6A-15-0420-M1	H6A-15-0420-M5	H6A-15-0420-M6
24	240	5	19½	H6A-15-0421-M1	H6A-15-0421-M5	H6A-15-0421-M6
32	240	5	24½	H6A-15-0422-M1	H6A-15-0422-M5	H6A-15-0422-M6
	480			H6A-15-0423-M1	H6A-15-0423-M5	H6A-15-0423-M6
40	240	5	30	H6A-15-0424-M1	H6A-15-0424-M5	H6A-15-0424-M6
	480			H6A-15-0425-M1	H6A-15-0425-M5	H6A-15-0425-M6
48	240	5	35	H6A-15-0426-M1	H6A-15-0426-M5	H6A-15-0426-M6
	480			H6A-15-0427-M1	H6A-15-0427-M5	H6A-15-0427-M6
64	240	5	45½	H6A-15-0428-M1	H6A-15-0428-M5	H6A-15-0428-M6
	480			H6A-15-0429-M1	H6A-15-0429-M5	H6A-15-0429-M6
80	240	5	56	H6A-15-0430-M1	H6A-15-0430-M5	H6A-15-0430-M6
	480			H6A-15-0431-M1	H6A-15-0431-M5	H6A-15-0431-M6