

SINGLE ENDED TUBULAR HEATERS

| SHEATH LENGTH | EFFECTIVE HEATED LENGTH* | WATTS | VOLTS | WATTS/SQ. IN. | CATALOG NUMBER |
|-------------------------------|--------------------------|-------|-------|---------------|----------------|
| .475" DIAMETER INCOLOY | | | | | |
| 15 $\frac{3}{4}$ | 13 | 500 | 240 | 26 | SEA1X-2025 |
| 19 $\frac{3}{4}$ | 17 | 675 | 240 | 26 | SEA2X-2026 |
| 23 $\frac{3}{4}$ | 21 | 850 | 240 | 27 | SEA2X-2027 |
| 27 $\frac{3}{4}$ | 25 | 1025 | 240 | 27 | SEA2X-2028 |
| 31 $\frac{3}{4}$ | 29 | 1225 | 240 | 28 | SEA3X-2029 |
| 35 $\frac{3}{4}$ | 33 | 1400 | 240 | 28 | SEA3X-2030 |
| 39 $\frac{3}{4}$ | 37 | 1575 | 240 | 28 | SEA3X-2031 |
| 43 $\frac{3}{4}$ | 41 | 1750 | 240 | 28 | SEA4X-2032 |
| 47 $\frac{3}{4}$ | 45 | 1925 | 240 | 28 | SEA4X-2033 |
| 51 $\frac{3}{4}$ | 49 | 2100 | 240 | 29 | SEA4X-2034 |
| 55 $\frac{3}{4}$ | 53 | 2275 | 240 | 29 | SEA5X-2035 |
| 59 $\frac{3}{4}$ | 57 | 2475 | 240 | 29 | SEA5X-2036 |
| 71 $\frac{3}{4}$ | 69 | 3000 | 240 | 29 | SEA6X-2037 |
| 83 $\frac{3}{4}$ | 81 | 3400 | 240 | 28 | SEA7X-2038 |
| 95 $\frac{3}{4}$ | 93 | 3000 | 240 | 22 | SEA8X-2039 |
| 107 $\frac{3}{4}$ | 105 | 2600 | 240 | 17 | SEA9X-2040 |
| 119 $\frac{3}{4}$ | 117 | 2300 | 240 | 13 | SEA10X-2041 |

* 1 $\frac{1}{2}$ " cold at bottom
 2 $\frac{1}{2}$ " cold at lead end