

TRIANGULATED CROSS SECTION TUBULAR HEATERS

| DIAMETER | A SHEATH LENGTH | B EFFECTIVE HEATED LENGTH | WATTS | VOLTS | CATALOG NUMBER |
|----------|-----------------|---------------------------|-------|----------|----------------|
| .475" | 20 | 13½ | 635 | 120 | A2T-2544 |
| | 27 | 20½ | 900 | 240 | A2T-2545 |
| | 28 | 21½ | 1000 | 240 | A2T-2546 |
| | 30 | 23½ | 1100 | 240 | A2T-2547 |
| | 36 | 29½ | 1350 | 240 | A3T-2548 |
| | 38 | 31½ | 1425 | 240 | A3T-2549 |
| | 40 | 33½ | 1500 | 240 | A3T-2550 |
| | 44 | 37½ | 1725 | 240 | A4T-1744 |
| | 46 | 39½ | 1800 | 240 | A4T-2551 |
| | 48 | 41½ | 1875 | 240 | A4T-2552 |
| | 50 | 43½ | 1950 | 240 | A4T-2553 |
| | 54 | 47½ | 2000 | 120 | A4T-2554 |
| | 54 | 47½ | 2000 | 240 | A4T-2555 |
| | 58 | 51½ | 2250 | 240 | A5T-2556 |
| | 60 | 53½ | 2500 | 240 | A5T-2557 |
| | 66 | 59½ | 2750 | 240 | A5T-2558 |
| | 70 | 63½ | 3000 | 240 | A6T-2559 |
| | 85 | 78½ | 3500 | 240 | A7T-2560 |
| 100 | 93½ | 4000 | 240 | A8T-2561 | |

| DIAMETER | A SHEATH LENGTH | B EFFECTIVE HEATED LENGTH | WATTS | VOLTS | CATALOG NUMBER |
|----------|-----------------|---------------------------|-------|----------|----------------|
| .375" | 18 | 11½ | 350 | 120 | J2T-2344 |
| | 20 | 13½ | 450 | 120 | J2T-2345 |
| | 22 | 15½ | 500 | 120 | J2T-2346 |
| | 25 | 18½ | 650 | 120 | J2T-2347 |
| | 25 | 18½ | 650 | 240 | J2T-2348 |
| | 27 | 20½ | 700 | 120 | J2T-2349 |
| | 27 | 20½ | 700 | 240 | J2T-2350 |
| | 28 | 21½ | 750 | 120 | J2T-2351 |
| | 28 | 21½ | 750 | 240 | J2T-2352 |
| | 32 | 25½ | 850 | 120 | J3T-2353 |
| | 32 | 25½ | 850 | 240 | J3T-2354 |
| | 34 | 27½ | 900 | 240 | J3T-2355 |
| | 36 | 29½ | 1000 | 120 | J3T-2356 |
| | 36 | 29½ | 1000 | 240 | J3T-2357 |
| | 38 | 31½ | 1050 | 120 | J3T-2358 |
| | 38 | 31½ | 1050 | 240 | J3T-2359 |
| | 40 | 33½ | 1100 | 240 | J3T-2360 |
| | 42 | 35½ | 1200 | 240 | J3T-2361 |
| | 44 | 37½ | 1250 | 240 | J4T-2362 |
| | 46 | 39½ | 1300 | 120 | J4T-2363 |
| | 46 | 39½ | 1300 | 240 | J4T-2364 |
| | 48 | 41½ | 1350 | 120 | J4T-2365 |
| | 48 | 41½ | 1350 | 240 | J4T-2366 |
| | 50 | 43½ | 1450 | 240 | J4T-2367 |
| | 54 | 47½ | 1550 | 120 | J4T-2368 |
| | 54 | 47½ | 1550 | 240 | J4T-2369 |
| | 58 | 51½ | 1700 | 240 | J5T-2370 |
| | 62 | 55½ | 1850 | 240 | J5T-2371 |
| | 66 | 59½ | 1950 | 120 | J5T-2372 |
| | 66 | 59½ | 1950 | 240 | J5T-2373 |
| | 70 | 63½ | 2100 | 120 | J6T-2374 |
| | 70 | 63½ | 2100 | 240 | J6T-2375 |
| | 74 | 67½ | 2250 | 240 | J6T-2376 |
| | 78 | 71½ | 2350 | 240 | J6T-2377 |
| 82 | 75½ | 2500 | 240 | J7T-2378 | |
| 86 | 79½ | 2600 | 240 | J7T-2379 | |
| 94 | 87½ | 2900 | 240 | J8T-2380 | |
| 98 | 91½ | 3000 | 240 | J8T-2381 | |

All items shown:
 30 watts/sq. in., Incoloy Sheath, C = 3/4"
 .475" diameter: D = 2½"
 .375" diameter: D = 1½"